

KamLAND-Zen



の状況と展望

福

東北大学ニュートリノ科学研究中心
井上邦雄

「宇宙の歴史をひもとく地下素粒子原子核研究」2017年領域研究会
2017年5月21日、岡山大学50周年記念館


Milestone



Experimental milestone has been a verification of KK-claim.
 KL-Zen+EXO-200 refuted it with fairly robust NME assumption.
 GERDA then clearly rejected it using the same ^{76}Ge .

What's next?

full coverage of Quasi Degeneracy → next milestone
full coverage of Inverted Hierarchy → next gen. exp.
full coverage of $m_{\text{lightest}} \sim 0$ (below 1 meV) → very difficult



We need to propose a future plan seeking below 10 meV.

comparison of double beta decay nuclei

Rodin et al., Nucl. Phys. A793 (2007)213-215

Nucleus	$T_{1/2}^{0\nu}$ (50 meV)	$T_{1/2}^{2\nu}$ measured (year)	Nat. Abundance (%)	Q-value (keV)	
$^{48}\text{Ca} \rightarrow ^{48}\text{Ti}$		$(4.2^{+2.1}_{-1.0}) \times 10^{19}$	0.19	4272	max. Q, fast 2ν
$^{76}\text{Ge} \rightarrow ^{76}\text{Se}$	0.86×10^{27}	$(1.5 \pm 0.1) \times 10^{21}$	7.8	2039	semiconductor
$^{82}\text{Se} \rightarrow ^{82}\text{Kr}$	2.44×10^{26}	$(0.92 \pm 0.07) \times 10^{20}$	9.2	2995	
$^{96}\text{Zr} \rightarrow ^{96}\text{Mo}$	0.98×10^{27}	$(2.0 \pm 0.3) \times 10^{19}$	2.8	3356	
$^{100}\text{Mo} \rightarrow ^{100}\text{Ru}$	2.37×10^{26}	$(7.1 \pm 0.4) \times 10^{18}$	9.6	3034	fast 2ν
$^{116}\text{Cd} \rightarrow ^{116}\text{Sn}$	2.86×10^{26}	$(3.0 \pm 0.2) \times 10^{19}$	7.5	2814	
$^{128}\text{Te} \rightarrow ^{128}\text{Xe}$	4.53×10^{27}	$(2.5 \pm 0.3) \times 10^{24}$	31.7	866	
$^{130}\text{Te} \rightarrow ^{130}\text{Xe}$	2.16×10^{26}	$(0.9 \pm 0.1) \times 10^{21}$	34.5	2527	large nat. abundance
$^{136}\text{Xe} \rightarrow ^{136}\text{Ba}$	4.55×10^{26}	$(2.3 \pm 0.1) \times 10^{21}$	8.9	2458	slow 2ν, rare gas
$^{150}\text{Nd} \rightarrow ^{150}\text{Sm}$	2.23×10 ²⁵	$(7.8 \pm 0.6) \times 10^{18}$	5.6	3371	0ν, fast 2ν

Notable nuclei

^{48}Ca highest Q, isotope enrichment is an issue


^{76}Ge semiconductor

^{136}Xe easy enrichment / purification, various detector technology

^{130}Te high natural abundance

^{150}Nd fast 0ν

KamLAND-Zen




Advantages of using KamLAND

- running detector
→ relatively **low cost and quick start**
- huge and clean (1200m^3 , U: $3.5 \times 10^{-18}\text{g/g}$, Th: 5.2×10^{-17})
→ negligible external gamma
(Xe and mini-balloon need to be clean)
- **Xe-LS can be purified**, mini-balloon replaceable if necessary, with relatively low cost
→ **highly scalable** (up to several tons of Xe)
- No escape or invisible energy from β , γ
→ BG identification relatively easy
- **anti-neutrino observation continues**
→ geo-neutrino w/o Japanese reactors


320kg 90% enriched ^{136}Xe installed for phase-I
and 380kg for phase-II

minimum inactive detector material
basically $25\mu\text{m-t}$ balloon film only



KamLAND-Zen started in 2011


only 2 years from initial funding (quick start!)





Unexpected BG has found

KamLAND-Zen Phase I (320kg xenon loading)

Thanks to full active apparatus,




Dominant BG identified as ^{110m}Ag




Xenon can be degassed from Xe-LS.
And ^{136}Xe on/off measurement has been demonstrated.
(useful for signal confirmation)

What can we do?



tripe fold coincidence
for ^{10}C rejection




dead time
free
electronics
MoGURA

purification !!


fine binning of volume

triple fold coincidence


future task



Phase-1 320kg
before
purification



Phase-2 380kg
after
purification
 $^{110\text{m}}\text{Ag}$
reduction
 $<1/10$



Event summary $2.3 < E < 2.7 \text{ MeV}$, $R < 1 \text{ m}$


	Period-1		Period-2		
	(270.7 days)		(263.8 days)		
Observed events		22		11	
Background	Estimated		Best-fit	Estimated	Best-fit
^{136}Xe $2\nu\beta\beta$...		5.48	...	5.29
		Residual radioactivity in Xe-LS			
^{214}Bi (^{238}U series)	0.23 ± 0.04		0.25	0.028 ± 0.005	0.03
^{208}Tl (^{232}Th series)	...		0.001	...	0.001
^{110m}Ag	...		8.5	...	0.0
		External (Radioactivity in IB)			
^{214}Bi (^{238}U series)	...		2.56	...	2.45
^{208}Tl (^{232}Th series)	...		0.02	...	0.03
^{110m}Ag	...		0.003	...	0.002
		Spallation products			
^{10}C	2.7 ± 0.7		3.3	2.6 ± 0.7	2.8
^6He	0.07 ± 0.18		0.08	0.07 ± 0.18	0.08
^{12}B	0.15 ± 0.04		0.16	0.14 ± 0.04	0.15
^{137}Xe	0.5 ± 0.2		0.5	0.5 ± 0.2	0.4

Phase-1 & 2 combined limit

$$T_{1/2}^{0\nu} > 1.07 \times 10^{26} \text{ yr}$$

!!!

$$\langle m_{\beta\beta} \rangle < (61 - 165) \text{ meV}$$



It also provides
upper limit of
 m_{lightest} at
180-480 meV.

Big leap toward IH !!

Our challenge continues!

Three dominant BGs; 2ν , “ ^{214}Bi on the film” and ^{10}C .

next target

further optimization of
triple-fold coincidence
and shower detection

We have purchased 800 kg of enriched xenon in total.

We have fabricated a larger mini-balloon with better measures against dusts.


We will resume the search with 750 kg of xenon.
To be called as “KamLAND-Zen 800”.

(Expected sensitivity is below 50 meV hoping to cover Yanagida’s prediction.)

Mini-balloon has been extracted. (Dec. 2015)

Zen 400

for tank investigation required by law



Xenon has been recovered
during recirculation and
deflation of the mini-balloon.



deflation →



2nd mini-balloon fabrication



cleaning, cleaning and
cleaning as usual



Example of improvements

before



after



clean
underwear



changing
room in a
clean room



cover
sheets



keep staying away
goggle
welding machine
cover sheet .
glove on glove
laundry twice a day .
clean underwear .




changing room in a clean room .
dust visualization
more neutralizer
. . .

laundry
twice a day





after Leak check and repair



New mini-balloon has been deployed and inflated with
“dummy” LS in last August

through characterization of mini-balloon

We confirmed that the mini-balloon is cleaner !!

Measures we took worked!

preliminary


$\times 10^{-12} \text{ g/g}_{\text{film}}$	^{232}Th	^{238}U
洗净直後	6	2^{Target}
This time*	$31+/-7$	$5.3+/-0.8$
Zen 400 1st	$79+/-3$	$14+/-1$
Zen 400 2nd	$336+/-2$	$46.1+/-4$

~1/10


At the same time, we noticed;

Indications of leak;

- camera image
- load cell
- balloon shape reconstruction with ^{210}Po events
- ^{222}Rn decay rate
- mixture of KL-LS and dummy-LS by gas-chromatography




回収したミニバルーンをHeリーク検出器で調べた。







補修した溶着部が割れている。



機械溶着ラインの端が避けている。




- ・機械溶着部は引き裂ける場所がある。
- ・手溶着部は簡単には裂けない。

最適パラメータの再探索

パラメータ：温度・時間・圧力、 (フィルム枚数、ヒーター方向、…)

測定量：降伏点・破断点、厚み、リーク、(…)


1cm幅での引っ張り強さと伸びの関係




圧力分布の測定 (懸案事項)

圧力は溶着線のエッジが高い

手溶着は圧力が低いが同じ傾向



マイクロスコープによる厚み測定



100→54 μm

Zen400用で手溶着をした技術者によるレビュー


圧力を下げる手溶着と同じ方向
から熱すれば大丈夫でしょう。。

降伏点に着目すると



例：230°C, 3sec, 0.1MPa

破断点に着目すると

例：240°C, 3sec, 0.1MPa



降伏点は、前回比50%~100%増
破断点は、前回比2倍



米国の技術者によるレビュー（技術提案）

オリジナル

ヒーターバンド



新手法



ヒーターバンド



オリジナル	~230°C	~3秒	4層
新手法	~170°C!	~10秒	2層


使用する6ナイロンの特性
融点225°C, ガラス転移点40°C
結晶化度30%, アモルファス70%

- 強度は手溶着と比べて遜色ない。
- エッジが強度低下しない。
- 作業手順の大幅簡略化。
- パラメータ調整は機器ごと必要。




Zen 800の今後の予定（目標）

- ・ 6月後半から溶着開始
- ・ 9月までにリークテストも完了
- ・ 10月くらいに導入
- ・ ダミーLSでテスト後、年内にキセノン導入
- ・ 年度内には不純物レベルも分かると期待する。
- ・ KamLAND2-Zenが予算化されるまで、最大5年程度継続。



And more future plans!

Higher energy resolution for reducing 2ν BG



1000+ kg xenon



Winston cone

light collection $\times 1.8$

high q.e. PMT
 $17''\phi \rightarrow 20''\phi$ $\varepsilon = 22 \rightarrow 30+\%$

New LAB LS
(better transparency)

light collection $\times 1.9$

light collection $\times 1.4$

expected $\sigma(2.6\text{MeV}) = 4\% \rightarrow \sim 2\%$

target sensitivity 20 meV

日本学術会議マスター・プラン2017に掲載

23-2 「極低放射能環境でのニュートリノ研究」


重点大型研究には入れず。。

R&D for KamLAND2-Zen and future


○ winston cone




○ HQE-PMT



○ New LAB-LS




○ denser xenon




principle confirmed

○ scintillator film




○ imaging



Summary

- KamLAND-Zen 400で手法の正当性を実証。(世界最高感度)
 $T_{1/2}^{0\nu} > 1.07 \times 10^{26} \text{ yr}$ $\langle m_{\beta\beta} \rangle < (61 - 165) \text{ meV}$ PRL117, 082503
- KamLAND-Zen 800のクリーン化を実証。Zen 400に対して
 フィルムの不純物量3分の1から10分の1を実現。
- リーク原因を調査し、溶着手法を改善。1.5から2倍程度の溶着
 強度を実現し、作業手順の簡略化も可能。
- 目標は今年度内にZen 800を稼働し、バックグラウンドレベル
 を測定する。目標感度は50meVをきり柳田予測に迫ること。
- KamLAND2-Zen の開発は順調。感度目標20meV

And more?



Super-KamLAND-Zen
in connection with Hyper-Kamiokande
target sensitivity 8 meV

Thank you!